

独立式真空吸料机 Stand alone vacuum suction machine



300G

性能特点：

- 体积小，重量轻，吸力强，可直接放置在料斗干燥机或其他原料容器上，完成自动吸料工作。
- 采用微电脑操作控制，操作使用方便。
- 选用进口名牌电机，噪音低、吸力大，质量可靠；
- 安装方便，操作便捷；
- 生产稳定，适合新料输送；
- 输送能力最高可达每小时300-400公斤，广泛使用在注塑机、挤出机等设备的原料输送行业中，能够实现完全自动化生产的辅助设备。

Features :

- Small size, light weight, strong suction, can be directly placed in the hopper dryer or other raw material containers, the completion of automatic suction work.
- The use of microcomputer operation and control, easy to use.
- The selection of imported brand-name motor, low noise, suction, quality and reliable; Easy to install, easy to operate;
- Production stability, suitable for new material transmission;
- The transmission capacity of up to 300-400 kg per hour, widely used in injection molding machines, extruders and other equipment, raw materials transportation industry, to achieve fully automated production of auxiliary equipment.

技术参数 Specification :

型号Model		HL-AL300G	HL-AL400G
马达Motor	型式Type	碳刷式Carbon brush type	感应式Induction type
	规格Specification	1.5KW/2HP 1Φ	1.5kw/2HP 3Φ
输送能力 (KG/H) Conveying capacity		300	330
吸料扬程 (M) Loading distance		3.5	4
静风压 (MM/H2O) Static wind pressure		1300	1400
储料桶容量 (L) Reservoir volume		7.5	10
送料管内径 (MM) Feed pipe diameter		Φ38	Φ38
配送料管 (MM) Distribution tube		Φ38mm×3.5m 1pcs	Φ38mm×4m 1pcs
外形尺寸Dimensions (CM)		34×34×59	45×37×66
		重量Weight (KG)	12

*以上规格如有变更，恕不另行通知，特殊规格可另行设计制造。Special design upon request.

分体式真空吸料机 Split type vacuum suction machine



700G

性能特点：

- 选用进口名牌电机，噪音低、吸力大，质量可靠。
- 体积小、重量轻、吸力强。
- 安装方便，操作方便。
- 输送能力最高可达每小时700-900公斤。
- 采用主机与料斗分离式设计，可搭配2个以上的料斗，实现一对多输送。
- 适用于长距离原料输送。

Features :

- Selection of imported brand-name motor, low noise, suction, quality and reliable
- Small size, light weight, strong suction,
- Easy to install, easy to operate,
- conveying capacity of up to 700-900 kg per hour,
- The use of separate host and hopper design, can be used with more than two hoppers, to achieve one-to-many transport.
- Suitable for long distance material transportation.

技术参数 Specification :

型号Model		HL-AL700G	HL-AL800G
马达Motor	型式Type	碳刷式Carbon brush type	感应式Induction type
	规格Specification	1.5kw/2HP 1Φ	1.5KW/2HP 3Φ
输送能力 (KG/H) Conveying capacity		310	450
吸料扬程 (M) Loading distance		4	4
静风压 (MM/H2O) Static wind pressure		1550	2100
储料桶容量 (L) Reservoir volume		7.5	7.5
送料管内径 (MM) Feed pipe diameter		Φ38	Φ38
配送料管 (MM) Distribution tube		Φ38mm×4m 2pcs	Φ38mm×4m 2pcs
外形尺寸Dimensions (CM)		主机Host	37 × 30 × 66
		料斗Hopper	28 × 34 × 43
重量Weight (KG)		14	47
		6	6

*以上规格如有变更，恕不另行通知，特殊规格可另行设计制造。Special design upon request.